

MUSTANG

SERIES


RIALTO
porcellanato

RIALTO
porcellanato

MUSTANG

SERIES





size

FINISHES

NATURAL
ANTI SILP

60x120cm
24"x48"

60x60cm
24"x24"

60x60**x2cm**
24"x24"

IVORY

FOUR
COLORS

IVORY



NATURAL 60x120cm 24"x48"



NATURAL 60x60cm 24"x24"



NATURAL 30x60cm 12"x24"



ANTI SLIP 60X60CM 24"x24"
60X60X**2CM** 24"x24"



MUS IVO01N
60x120cm 24"x48"



MUS SIL05N
MUS GRE06N
60x120cm 24"x48"



WALL MUS GRE06N 60x120cm 24"x48"
FLOOR MUS SIL05N 60x60cm 24"x24"



NATURAL 60x120cm 24"x48"



NATURAL 60x60cm 24"x24"



ANTI SLIP 60X60CM 24"x24"
60X60X2CM 24"x24"



NATURAL 30x60cm 12"x24"



MUSTANG SERIES





MUS GRE06N
60x120cm 24"x48"
60x60x2cm 24"x24"



NATURAL 60x120cm 24"x48"



NATURAL 60x60cm 24"x24"



ANTI SLIP 60X60CM 24"x24"
60X60X2CM 24"x24"



NATURAL 30x60cm 12"x24"

MUSTANG SERIES



MUS GRE06N
60x60cm 24"x24"



MUS GRE06N
60x60cm 24"x24"




MUS BLK09N
60x120cm 24"x48"

MUSTANG SERIES


BLACK




NATURAL 60x120cm 24"x48"



NATURAL 60x60cm 24"x24"



NATURAL 30x60cm 12"x24"



ANTI SLIP 60X60CM 24"x24"
60X60X**2CM** 24"x24"



WALL MUS SIL05N 60x120cm 24"x48"
FLOOR MUS BLK09N 60x120cm 24"x48"



MUS BLK09N
60x120cm 24"x48"



MUSTANG SERIES



MUS BLK09N
60x60cm 24"x24"



IVORY MUS IVO01N



NATURAL 60x120cm



NATURAL 60x60cm



ANTI SLIP 60X60CM
60X60X**2CM**

SILVER MUS SIL05N



NATURAL 60x120cm



NATURAL 60x60cm



ANTI SLIP 60X60CM
60X60X**2CM**

GREY MUS GRE06N



NATURAL 60x120cm



NATURAL 60x60cm



ANTI SLIP 60X60CM
60X60X**2CM**

BLACK MUS BLK09N



NATURAL 60x120cm



NATURAL 60x60cm



ANTI SLIP 60X60CM
60X60X**2CM**

Technical specifications



UNE-EN ISO 10545	Test Standard ISO 13006-EN1441	Product Standard RIALTO VALUES	QUARTZ RIALTO VALUES	QUARTZ x2 RIALTO VALUES
------------------	-----------------------------------	-----------------------------------	-------------------------	-----------------------------------

Caratteristiche dimensionali /
Dimensional and surface appearance

Spessore / Thickness	ISO 10545-2	± 5 %	± 3 %	± 3 %
Lunghezza e larghezza / Lenght and width	ISO 10545-2	± 0,5 %	± 0,2 %	± 0,2 %
Ortogonalità / Squareness	ISO 10545-2	± 0,6 %	± 0,2 %	± 0,2 %
Planarità / Surface flatness	ISO 10545-2	± 0,5 %	± 0,2 %	± 0,2 %

Proprietà fisiche / Phisical Properties

Assorbimento d'acqua / Water absorption	ISO 10545-3	≤ 0,5 %	0,08 %	0,09 %
Resistenza a flessione N/mm ² / Moduls of rupture N/mm ²	ISO 10545-4	≥ 35 N/mm ²	42 N/mm ²	N/A
Sforzo di rottura N / Breaking strength N	ISO 10545-4	≥ 1300 N	2300 N	10000 N
Resistenza agli sbalzi termici / Resistance to thermal shock	ISO 10545-9	REQUIRED	PASS	PASS
Resistenza al gelo / Frost resistance	ISO 10545-12	REQUIRED	PASS	PASS
Antiscivolo / Antislip 120x60/60x60/30/60	DIN51130	-	R9	-
Ramp 60x60/60x60x2	DIN51130	-	R11	R11

Proprietà chimiche / Chemical properties

Resistencia agli prodotti di pulizia e additivi / Resistance to household chemical and swimming pool	ISO 10545-13	Min. GB/UB	UA	UA
Resistenza agli acidi ed alle basi (concentrazione leggera) / Resistance to acids and alkalis (low concentration)	ISO 10545-13	GLB/ULB	ULA	ULA
Resistenza agli acidi ed alle basi (concentrazione alta) / Resistance to acids and alkalis (high concentration)	ISO 10545-13	GHB/UHB	UHA	UHA
Resistenza alle macchie / Resistance to staining	ISO 10545-14	Min. 3	CLASS 5	CLASS 5

